



G-Box Expert GL-4 75W-90, 80W-85

Description

Formulated with combination of high quality synthetic and mineral base oils and progressive additives, semi-synthetic *G-Box Expert GL-4 75W-90* and mineral *G-Box Expert GL-4 80W-90* gear oils are designed to deliver excellent lubrication in manual transmissions of cars and trucks. The products provide wide temperature range of operation and guarantee long transmission life.

Benefits

- Optimal anti-friction properties prevent vibration
- Outstanding low temperature characteristics guarantee trouble-free operation at down to -40°C (SAE 75W-90)
- High thermal stability extends oil drain interval
- High wear resistance ensures reliable protection of friction pairs and prolongs their life
- Compatibility with seal materials used in modern equipment
- Excellent corrosion preventive properties
- Superior resistance to foaming

Applications

- Manual gearboxes of cars and transfer cases of four-wheel drive vehicles containing spur, bevel and spiral-bevel gears
- Mechanisms running under medium load conditions and requiring the use of API GL-4 motor oils
- G-Box Expert GL-4 80W-85 is recommended for lubricating manual gearboxes in VAZ front-wheel drive cars

Specifications and Approvals

G-Box Expert GL-4 75W-90, 80W-85 are approved by:

- MB 235.1*
- ZF TE-ML 02B*, 17A*
- AVTOVAZ

G-Box Expert GL-4 75W-90, 80W-85 meet the requirements:

- API GL-4

** G-Box Expert GL-4 80W-85 only*



All products may not be available locally. For more information please contact your local sales office, our technical personnel techservice@gazprom-neft.ru or visit our website www.gazpromneft-lubricants.com. Due to continual product research and development, the information contained herein is subject to change without notification. Typical properties may vary slightly.
© 2009 Gazpromneft – Lubricants Ltd. All rights reserved.
28.10.2013

Typical Properties

G-Box Expert GL-4 75W-90, 80W-85

| Viscosity, | | 75W-90 | 80W-85 |
|----------------------------------|------------|--------|--------|
| • cSt @ 40°C | GOST 33 | 102.7 | 109.1 |
| • cSt @ 100°C | GOST 33 | 16.4 | 12.8 |
| VI | GOST 25371 | 170 | 95 |
| Flash Point, COC, °C | GOST 4333 | 208 | 208 |
| Pour Point, °C | GOST 20287 | -42 | -34 |
| Density @ 15°C kg/m ³ | GOST 2896 | 881 | 889 |

Health and Safety

When used as directed, G-Box Expert GL-4 75W-90 and 80W-85 have no adverse effects either on health or environment. Beyond normal hygiene no special precautions are required. Avoid contact with skin. Wear protective gloves. In case of contact, flush immediately with water and soap. For more information please refer to the Safety Data Sheet.

Reduced Environmental Impact

Place used product in an appropriate waste disposal container. Dispose via a licensed waste disposal contractor. Do not discharge waste lubricant into groundwater, watercourses, soil, sewerage or drainage systems.

